



Turbo Chain Oils

Turbo Chain Oils are designed specifically to protect the bars and chains of the high performance, professional power saws used in the Canadian woodlands. These saws are subjected to severe operating conditions in high speed, high volume, logging operations where the highest factors of performance and reliability are demanded from fuels, lubricants and the saws themselves.

Turbo Chain Oils are available in grades, Winter and Summer, for use under all seasonal conditions. They are blended from HVI base stocks and contain an additive system essential to the protection of the power saw chain.

Chain and bars are subject to sliding friction, which can displace a normal oil film in a very short time. **Turbo Chain Oils** have a special tackifier that ensures that the film of oil ejected onto the operating chain does not fling off. All grades provide anti-rust and storage protection.

Turbo Chain Oils should not be used as engine oil in the power heads of saws.

They are dyed a distinctive red colour so that saw operators will be able to differentiate between “chain” and “engine” oils.

Typical Properties

Properties	Turbo Chain Oil Winter	Turbo Chain Oil Summer
Colour	Red	Red
Appearance	Tacky	Tacky
Viscosity cSt @ 40 °C	58.0	130
Flash Point, ° C	180	200
Pour Point, ° C	-21	0

The values quoted above are typical of normal production and they do not constitute a specification.

Product Availability

Package	Turbo Chain Oil Winter	Turbo Chain Oil Summer
205-L Drum	•	•
3.78-L Jug	•	•

Due to continual research and development, the information contained herein is subject to changes without notification.